

Global Manufacturing- Split Bolt Connectors



Features

Our Global Manufacturing Split Bolt Connectors are used in order to join 2 copper wires in power or grounding electrical connection applications. Copper alloy bolt and nut construction provides reliable protection where corrosive elements are present.



Sizing and Features

| Product | Size | Product Description | Box Qty. | Outer Diameter | |
|----------|--------|----------------------|----------|----------------|----------|
| | | | | Min. | Max. |
| G-KSU6 | 6 | Split Bolt Connector | 100 | 6STRSOL | 14STRSOL |
| G-KSU4 | 4 | Split Bolt Connector | 100 | 4STRSOL | 14STRSOL |
| G-KSU3 | 3 | Split Bolt Connector | 100 | 3STRSOL | 14STRSOL |
| G-KSU2 | 2 | Split Bolt Connector | 100 | 2STRSOL | 14STRSOL |
| G-KSU1/0 | 1/0 | Split Bolt Connector | 50 | 1/0STRSOL | 14STRSOL |
| G-KSU2/0 | 2/0 | Split Bolt Connector | 25 | 2/0STRSOL | 14STRSOL |
| G-KSU3/0 | 3/0 | Split Bolt Connector | 25 | 3/0STRSOL | 8STRSOL |
| G-KSU250 | 250MCM | Split Bolt Connector | 25 | 250STR | 8STR |
| G-KSU350 | 350MCM | Split Bolt Connector | 6 | 350STR | 1/0STR |
| G-KSU500 | 500MCM | Split Bolt Connector | 6 | 500STR | 2/0STR |

- Features copper pressure bar and hex style head
- Highly resistant to corrosion and cracking
- Provides high contact pressure between conductors
- Suitable for Direct Burial
- Copper Alloy

