Global Manufacturing- Yellow Pulling Rope

Features

Our Global Manufacturing Yellow Pulling Rope is made of polypropylene for longer durability and strength. It is a rugged, lightweight and mildew resistant rope. This low friction rope slides easily through conduit and piping without being snagged. It features a unique braided design which ensures strength and resistance to rot, mildew and stretching. It comes in varied tensile strengths and lengths to meet the needs of any job application.

Sizing and Features

Product	Size	Product Description	Box Qty.
GYR316250	3/16"	Yellow - 250'	
GYR316600	3/16"	Yellow - 600'	
GYR3161000	3/16"	Yellow - 1000'	
GYR14250	1/4"	Tensile Strength - 1130 - 250'	
GYR14600	1/4"	Tensile Strength - 1130 - 600'	
GYR141200	1/4"	Tensile Strength - 1130 - 1200'	
GYR142400	1/4"	Tensile Strength - 1130 - 2400'	
GYR516600	5/16"	Tensile Strength - 1710 - 600'	
GYR5161200	5/16"	Tensile Strength - 1710 - 1200'	
GYR38250	3/8"	Tensile Strength - 2440 - 250'	
GYR38600	3/8"	Tensile Strength - 2440 - 600'	
GYR381200	3/8"	Tensile Strength - 2440 -1200'	
GYR382400	3/8"	Tensile Strength - 2440 - 2400'	
GYR12250	1/2"	Tensile Strength - 3780 - 250'	
GYR12600	1/2"	Tensile Strength - 3780 - 600'	
GYR12600W	1/2"	Tensile Strength - 3780 - 600'	
GYR121200	1/2"	Tensile Strength - 3780 - 1200'	
GYR58250	5/8"	Tensile Strength - 5600 - 250'	
GYR58600	5/8"	Tensile Strength - 5600 - 600'	
GYR581200	5/8"	Tensile Strength - 5600 - 1200'	
GYR34250	3/4"	Tensile Strength - 7650 - 250'	
GYR34600	3/4"	Tensile Strength - 7650 - 600'	
GYR341200	3/4"	Tensile Strength - 7650 - 1200'	



- Low-friction polypropylene rope slides easily through conduit
- Non-sliver surface can be handled without gloves
- Will not rot or mildew
- Rugged, lightweight construction

Global Manufacturing
6315 Traffic Avenue, Ridgewood, NY 11385 | 718.257.2111