

Global Manufacturing- Liquid-Tite



Features

Our Global Manufacturing Liquid-lite is designed for use in continuous-flex applications. It is flexible and features an inner core with woven nylon mesh reinforcement. Our Liquid-lite varies in sizes from 1/2"- 4" and is offered in varying quantities between 50' and 1000'. It also comes available in a carton or in a full reel.



Sizing & Features

Product	Size	Description	Qty	Inner Diameter		Outer Diameter	
				Min.	Max.	Min.	Max.
UL0500-100	1/2"	UL Liquid-Tite, Carton	100	.622	.642	.820	.840
UL0500-500	1/2"	UL Liquid-Tite, Reel	500	.622	.642	.820	.840
UL0750-100	3/4"	UL Liquid-Tite, Carton	100	.820	.840	1.030	1.050
UL0750-500	3/4"	UL Liquid-Tite, Reel	500	.820	.840	1.030	1.050
UL1000-100	1"	UL Liquid-Tite, Carton	100	1.041	1.066	1.290	1.315
UL1000-400	1"	UL Liquid-Tite, Reel	400	1.041	1.066	1.290	1.315
UL1250-050	1-1/4"	UL Liquid-Tite, Carton	50	1.380	1.410	1.630	1.660
UL1250-250	1-1/4"	UL Liquid-Tite, Reel	250	1.380	1.410	1.630	1.660
UL1500-050	1-1/2"	UL Liquid-Tite, Carton	50	1.575	1.600	1.865	1.900
UL1500-150	1-1/2"	UL Liquid-Tite, Reel	150	1.575	1.600	1.865	1.900
UL2000-050	2"	UL Liquid-Tite, Carton	50	2.020	2.045	2.340	2.375
UL2000-100	2"	UL Liquid-Tite, Reel	100	2.020	2.045	2.340	2.375
UL2500-025	2-1/2"	UL Liquid-Tite, Carton	25	2.480	2.505	2.840	2.875
UL3000-025	3"	UL Liquid-Tite, Carton	25	3.070	3.100	3.460	3.500
UL3500-025	3-1/2"	UL Liquid-Tite, Carton	25	3.500	3.540	3.960	4.000
UL4000-025	4"	UL Liquid-Tite, Carton	25	4.000	4.040	4.460	4.500

- Flexible Steel Conduit
- Sunlight resistant
- Flame Retarded PVC Jacket
- Hot Dipped Zinc Galvanized low carbon steel core

