

Conduit Fittings- Conduit Hanger



Features

Conduit Hangers are used to securely connect EMT or Rigid conduit directly to the mounting surface of choice. These hangers are rated for indoor and outdoor use and are fabricated with long-lasting steel with zinc plating. This hanger includes the nut and bolt for connection.

- Zinc Die Cast
- Corrosion Resistant
- Use with locknuts
- Seives are a short raceway between electrical enclosures



Sizing and Features

Product	Size	Description	Dimensions				
			Qty	A	B	C	D
G-HB50	½"	Conduit Hanger W/ Nut & Bolt	100	1.875	.750	.725	.25
G-HB75	¾"	Conduit Hanger W/ Nut & Bolt	100	2.125	.750	.850	.25
G-HB100	1"	Conduit Hanger W/ Nut & Bolt	100	2.437	.875	.975	.25
G-HB125	1-¼"	Conduit Hanger W/ Nut & Bolt	100	2.75	.875	.975	.25
G-HB150	1-½"	Conduit Hanger W/ Nut & Bolt	100	2.875	.875	1.050	.25
G-HB150G	1-½"	Conduit Hanger W/ Nut & Bolt (GAL)	100	3.125	1.000	1.125	.25
G-HB200	2"	Conduit Hanger W/ Nut & Bolt	50	3.875	1.000	1.145	.25
G-HB250	2-½"	Conduit Hanger W/ Nut & Bolt	50	4.625	1.225	1.225	.3125
G-HB300	3"	Conduit Hanger W/ Nut & Bolt	25	5.500	1.275	1.275	.3125
G-HB350	3-½"	Conduit Hanger W/ Nut & Bolt	25	5.750	1.275	1.275	.3125
G-HB400	4"	Conduit Hanger W/ Nut & Bolt	25	6.250	1.275	1.275	.3125



Trade Size	Metric Designator	Pull Force (Load Rating)					
		Electrical Metallic Tubing (EMT)		Rigid Metal Conduit (RMC) Intermediate Metal Conduit (IMC)		Rigid PVC conduit	
		Pull Force (lbf)	Reference Load Rating (lb)	Pull Force (lbf)	Reference Load Rating (lb)	Pull Force (lbf)	Reference Load Rating (lb)
1/2"	(16)	150	50	150	50	150	50
3/4"	(21)	150	50	150	50	150	50
1"	(27)	190	60	190	60	160	50
1-1/4"	(35)	225	75	225	75	175	55
1-1/2"	(41)	250	80	250	80	180	60
2"	(53)	300	100	300	100	200	65
2-1/2"	(63)	375	125	375 475	125 160	250	80
3"	(78)	500	160	500 875	165 295	300	100
3-1/2"	(91)	600	200	600 1125	200 375	375	125
4"	(103)	700	230	700	230	450	150