

Global Manufacturing- Rubber Cord Connectors



Features

Our Global Manufacturing line of Rubber Cord Connectors are designed to secure a power supply cord to a piece of electrical equipment. This fitting is offered from 1/2" - 1" and vary for cable at diameters .250 - .985 .



Sizing and Features

Product	Size	Product Description	Box Qty	Dimensions			
				A	Min	Max	B
G-GC50A250	1/2"	Rubber Cord Conn., Cable .250	25	.96	.19	.260	1.30
G-GC50A375	1/2"	Rubber Cord Conn., Cable .375	25	.96	.26	.375	1.30
G-GC50A500	1/2"	Rubber Cord Conn., Cable .500	25	.96	.375	.500	1.30
G-GC75A500	3/4"	Rubber Cord Conn., Cable .500	25	1.20	.44	.500	1.32
G-GC75A625	3/4"	Rubber Cord Conn., Cable .625	25	1.20	.50	.625	1.32
G-GC75A750	3/4"	Rubber Cord Conn., Cable .750	25	1.20	.625	.725	1.32
G-GC100A750	1"	Rubber Cord Conn., Cable .750	10	1.51	.625	.750	1.58
G-GC100A880	1"	Rubber Cord Conn., Cable .800	10	1.51	.750	.880	1.58
G-GC100A985	1"	Rubber Cord Conn. Cable .985	10	1.51	.875	.985	1.58

- Zinc Die Cast
- Indoor and Outdoor Use
- Provides Excellent Strain Relief
- Prevents Cable Pullout
- Provides tight seal against Elemental Damage
- UL Listed

