

Conduit Fittings- M.I. Right Angle Support




Features

M.I. Conduit Supports are designed to fasten a run threaded rigid or IMC conduit along a right angled bend. Right Angle conduit clamps are used to mount EMT or Rigid conduit across or perpendicular to beam, channel or angle supports. They are die-cast with corrosion resistant zinc alloy.



Sizing and Features

Product	Size	Description	Qty	Sizes		
				A	B	C
G-KRA50M	1/2"	M.I. Iron Support	50	1.00	1.25	2.50
G-KRA75M	3/4"	M.I. Iron Support	50	1.125	1.125	2.8125
G-KRA100M	1"	M.I. Iron Support	50	1.375	1.375	3.0625
G-KRA125M	1-1/4"	M.I. Iron Support	50	1.75	1.75	3.1875
G-KRA150M	1-1/2"	M.I. Iron Support	50	2.00	2.375	3.50
G-KRA200M	2"	M.I. Iron Support	25	2.50	2.50	4.50
G-KRA250M	2-1/2"	M.I. Iron Support	25	3.00	3.00	4.875
G-KRA300M	3"	M.I. Iron Support	10	3.625	3.875	5.375
G-KRA350M	3-1/2"	M.I. Iron Support	10	4.0625	4.5625	5.875
G-KRA400M	4"	M.I. Iron Support	10	4.6875	5.0625	6.6875



- Heavy Duty Galvanized U-Bolt
- Provides a secure connection and tight clamping action capable of withstanding heavy loads
- Zinc Plated
- Malleable Iron
- Galvanized Steel Hardware
- UL Listed

