



PRODUCT SPECIFICATION SHEET

Greenfield UL Flex Conduit

Features

Our Global Manufacturing Greenfield Flex Conduit is a non-jacketed flexible conduit has many universal wiring applications.

It is often referred to as Reduced Wall Flex.

Our Greenfield varies in sizes from 3/8" - 4" and is offered in varying quantities between 25' and 1000'



Size and Features

Product	Size	Qty	Inner Diameter		Outer Diameter	
			Min.	Max.	Min.	Max.
GFUL0375-100	3/8"	100	0.484	0.504	0.689	0.709
GFUL0375-250	3/8"	250	0.484	0.504	0.689	0.709
GFUL0375-1000	3/8"	1000	0.484	0.504	0.689	0.709
GFUL0500-100	1/2"	100	0.622	0.642	0.819	0.839
GFUL0500-1000	1/2"	1000	0.622	0.642	0.819	0.839
GFUL0750-100	3/4"	100	0.815	0.835	1.032	1.051
GFUL0750-500	3/4"	500	0.815	0.835	1.032	1.051
GFUL1000-50	1"	50	1.032	1.055	1.287	1.315
GFUL1000-400	1"	400	1.032	1.055	1.287	1.315
GFUL1250-50	1-1/4"	50	1.37	1.394	1.63	1.661
GFUL1250-250	1-1/4"	250	1.37	1.394	1.63	1.661
GFUL1500-25	1-1/2"	25	1.579	1.598	1.866	1.902
GFUL1500-1500	1-1/2"	150	1.579	1.598	1.866	1.902
GFUL2000-25	2"	25	2.02	2.043	2.339	2.374
GFUL2000-50	2"	50	2.02	2.043	2.339	2.374
GFUL2000-100	2"	100	2.02	2.043	2.339	2.374
GFUL2500-25	2-1/2"	25	2.48	2.504	2.839	2.874
GFUL3000-25	3"	25	3.07	3.098	3.46	3.5
GFUL3500-25	3-1/2"	25	3.55	3.576	3.95	3.995
GFUL4000-25	4"	25	4	4.039	4.457	4.5

- Crush and corrosion resistant steel core for lasting mechanical protection
- High mechanical strength
- Temperature range is from -15° C - +70° C



Global Manufacturing

63-15 Traffic Ave, Ridgewood New York, 11385 | 718-253-2111

WARSHAW

INCORPORATED