

Conduit Fittings- Insulated Grounding Bushings



Features

Insulated conduit bushings are used along with locknuts to connect threaded Rigid/IMC conduits to boxes or enclosures. This allows for quick installation of bonding jumper to Rigid or IMC conduit. The plastic liner prevents damage to wire insulation.



Sizing and Features

Product	Size	Description	Qty	Wire Capacity	
				Min	Max
G-MLGB050M	1/2"	Insulated Grounding Bushing	50	14	4
G-MLGB075M	3/4"	Insulated Grounding Bushing	50	14	4
G-MLGB100M	1"	Insulated Grounding Bushing	25	14	4
G-MLGB125M	1-1/4"	Insulated Grounding Bushing	20	14	4
G-MLGB150M	1-1/2"	Insulated Grounding Bushing	25	14	4
G-MLGB200M	2"	Insulated Grounding Bushing	25	14	4
G-MLGB250M	2-1/2"	Insulated Grounding Bushing	10	14	4
G-MLGB300M	3"	Insulated Grounding Bushing	10	14	4
G-MLGB350M	3-1/2"	Insulated Grounding Bushing	10	14	4
G-MLGB400M	4"	Insulated Grounding Bushing	10	14	4

- Zinc Die Cast
- Zinc Plated Steel Screws
- Plastic Metaliner rated to 150° F
- UL Listed

